

NATUREWALK

Floors & Walls



Description

NatureWalk is a self adhesive woven polyester suitable for floors, walls & windows. Direct print with R10 non-slip certification so no overlaminated is required when used on floors. Can be applied to most indoor flooring surfaces including carpet. Also suitable for many indoor wall surfaces. NatureWalk is PVC free and 100% recyclable

Features & Benefits

- Suitable for multiple indoor floor surfaces including carpet
- Direct print R10 textured non-slip surface, no overlaminate required
- Suitable as indoor wall covering for multiple surfaces
- Stunning print quality
- Excellent dimensional stability (polyester)
- Flame retardant
- Removes cleanly
- Non PVC & recyclable
- Printable on UV, latex, solvent & eco solvent

Surfaces

- | | |
|--|---|
| <p>Floor (indoors)</p> <ul style="list-style-type: none"> - Tiles - Vinyl - Lino - Floorboards - Carpet | <p>Walls & Windows(indoors)</p> <ul style="list-style-type: none"> - Plasterboard - Glass |
|--|---|

Non -Slip Certification

R10 non-slip certification

Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix or Visionary Digital be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specific applications.

Applications

- Floor & Wall/Window Graphics
- Exhibition
- POS / POP
- Green signage solution

Durability

NatureWalk durability depends on many factors including the surface it is applied to and the frequency of abrasive forces. Please see guide below;

- Floor (indoor)
- > Low Traffic - 6+ months
 - > High Traffic - 3 months

- Wall & Window (indoor)
- > 24 months +

Technical Information

Size Width: 1.372m
 Length: 50m
 Print Method: UV, Latex & Solvent
 Adhesive: Blockout acrylic adhesive