

Pform Removable Block-Out SAV



Features

REMOV-
ABLE

BLOCK
OUT

GLOSS

DOUBLE
PE LINER

REAL
ESTATE
BOARDS

MATCHED
LAMs

BEST
VALUE

Description

Pform monomeric, removable, block-out self-adhesive vinyl combines performance + value & is #1 for real estate board signage. This promotional grade SAV features an excellent white point, solvent adhesive, double PE liner, clean removal for up to 12 months, matching laminates and is exceptional value.

Features & Benefits

- Excellent white point & vibrant print
- Solvent based adhesive, removable for up to 12 months
- Double PE liner suitable for solvent, UV & Latex printing
- Good dimensional stability after installation
- Matched laminates available
- Perfect for real estate board signage
- Excellent value

Applications

- Real estate signage
- Hoardings
- Retail, window & point of sale

Durability

1 year removable

Warranty

Pform products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Pform materials found to not meet our product specifications. In no case shall Pform or Visionary Digital be liable for any direct, indirect, or consequential damages, including labor or non Pform materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specific applications.

Technical Information

Size Width: 1.37m & 1.52m

Length: 50m (custom lengths available up to 250m)

Material: Monomeric calendered PVC

Thickness: 100 micron

Adhesive: Grey removable solvent adhesive

Adhesion (N/25mm): a) Initial: >5N and b) 24 hr peel at 180 degrees >7N

Liner: 140gsm double sided PE

Dimensional Stability MD: <1.2mm / CD:<1mm

Tensile Strength (N/25mm) MD: >45mm / CD:>40mm

Application Temperature(Celcius): -20~+70 C

Testing Conditions: Indoor temp 23 C, rel humidity 50% applied to glass

Pform Permanent Block-Out SAV



Features

PERMA-
NENT

BLOCK
OUT

GLOSS

DOUBLE
PE LINER

REAL
ESTATE
BOARDS

MATCHED
LAMs

BEST
VALUE

Description

Pform monomeric, permanent, block-out self-adhesive vinyl combines performance + value & is #1 for real estate board signage. This promotional grade SAV features an excellent white point, solvent adhesive, double PE liner, and matching laminates and is exceptional value.

Features & Benefits

- Excellent white point & vibrant print
- Solvent based adhesive, permanent adhesive
- Double PE liner suitable for solvent, UV & Latex printing
- Good dimensional stability after installation
- Matched laminates available
- Perfect for real estate board signage
- Excellent value

Applications

- Real estate signage
- Hoardings
- Retail, window & point of sale

Durability

1 year

Warranty

Pform products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Pform materials found to not meet our product specifications. In no case shall Pform or Visionary Digital be liable for any direct, indirect, or consequential damages, including labor or non Pform materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specific applications.

Technical Information

Size Width: 1.37m & 1.52m
 Length: 50m (custom lengths available up to 250m)
 Material: Monomeric calendered PVC
 Thickness: 100 micron
 Adhesive: Grey permanent solvent adhesive
 Adhesion (N/25mm): a) Initial: >5N and b) 24 hr peel at 180 degrees >7N
 Liner: 140gsm double sided PE
 Dimensional Stability MD: <1.2mm / CD:<1mm
 Tensile Strength (N/25mm) MD: >45mm / CD:>40mm
 Application Temperature(Celcius): -20~+70 C

Testing Conditions: Indoor temp 23 C, rel humidity 50% applied to glass