

Decortex Textile Wall Graphic



Features

TEXTILE
FINISH

REMOV-
ABLE

HIGH
OPACITY

PVC
FREE



COST
EFFECTIVE

Description

Decortex is the preferred self-adhesive print film for graphic wall market. A combination of subtle textile finish, removability, high opacity base film and outstanding print performance is why interior designers prefer Decortex for their wall graphics projects. Made from polyester Decortex can be butt joined for a seamless finish, is PVC-free and can be recycled with the appropriate recycling program.

Features & Benefits

- Textile finish
- High opacity base film hides wall imperfections
- Removable adhesive *
- Excellent dimensional stability & can be butt joined
- Suitable for indoor & outdoor
- Suitable for Solvent, UV & Latex printing
- PVC-Free
- Recyclable with appropriate recycling program

Applications

- Commercial & residential wall graphics
- General signage requiring PVC-Free alternative

Removability

- Removable up to 6 months

Durability

- Indoors - 5 yrs
- Outdoors - 3 yrs

Warranty

Pform products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Pform materials found to not meet our product specifications. In no case shall Pform or Visionary Digital be liable for any direct, indirect, or consequential damages, including labor or non Pform materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specific applications.

Test First

*We recommend testing Decortex on all surfaces prior to installing, especially painted surfaces. In some instances paint may be removed upon removal.

Technical Information

Size Width: 1.37m

Length: 50m

Material: Polyester

Base Fabric Yarn: 150D x 150D

Adhesive: Grey removable adhesive

Adhesion (N/25mm): a) Initial: >2-5N and b) 24 hr peel at 180 degrees >3-6N

Liner: 160gsm Double PE liner

Tensile Strength (N/5cm) MD: >400mm / CD: >400mm

Tearing Strength at Break (N/5cm) MD: >20 / CD: >10

Application Temperature(Celcius): -20~+70 C

Testing Conditions: Indoor temp 23 C, rel humidity 50% applied to glass