


TexWalk®

The multi-surface floor decal solution



Applications



Description

TexWalk is a revolutionary new floor media suitable for a wide range of flooring surfaces indoors & outdoors. Indoors suitable for low pile carpet, stone, lino etc. Outdoors suitable for smooth tiles and smooth concrete etc. TexWalk has a built-in textured non slip surface and does not require an overlamine. No overlamine means it's considerably faster to market plus colours are significantly brighter. Comes with an R12 non slip certification (CSIRO).

Features & Benefits

- Suitable for almost every surface indoors & outdoors*
- Built-in textured non-slip surface eliminates overlamination so super fast to produce
- R12 CSIRO non slip certification means every stays safe
- Proven performance - print quality, reliability, durability & removal
- Printable on UV, Solvent & Latex

Surfaces

Indoor Floor
> Carpet (low pile)
> Concrete
> Porous Stone
> Tiles

Outdoor Ground
> Concrete
> Tiles
> Asphalt
> Pavers
> Porous Stone

Indoor Wall
> Plasterboard
> MDF
> Concrete

Outdoor Wall
> Concrete
> Brick

Slip Resistance

CSIRO approved R12 certification
Australian / New Zealand standards AS 4586:2013

Test First

Every surface is different and changes with time so we recommend trailing first with a small piece in a inconspicuous location. Trial over a minimum 4 week period to determine suitability for the intended

* TexWalk is not suitable for ultra smooth surfaces such as highly polished stone & glossy tiles etc

Applications

- Retail
- Shopping Centres
- Activations
- Footpath Promotions
- Concrete / brick walls
- Exhibitions
- Sporting Events
- Building Wraps

Durability

TexWalk durability depends on many factors including the surface it is applied to and the frequency of abrasive forces. Please see guide below;

Indoor Floor
> Low Traffic - 6 months
> High Traffic - 3 months

Outdoor Floor
> Low Traffic - 4 months
> High Traffic - 1 month

Indoor Wall
> 24 months +

Outdoor Wall
> 12 months +

Technical Information

Size Width: 1.22m
Length: 25m & 50m

Warranty

Since there is no control under which conditions the product has been applied or has been used, all product warranty automatically end as soon as the product has been applied to any surface