

PROMO NON-SLIP FLOOR LAMINATE - R9



FEATURES

R9
NON-SLIP
APPROVED

BEST
VALUE

GLARE
REDUCTION

SUITABLE
FOR
UV, LATEX
SOLVENT

Description

Pform Promo Non-Slip Floor Laminate R9 is an *indoor *short term *promotional grade *low cost *non-slip approved *floor decal laminate. Comes with R9 / P3 non-slip certification. Durability for up to 12 months with moderate foot traffic.

Features & Benefits

- Cost effective indoor floor decal laminate
- Suitable for most indoor flat & smooth surfaces
- R9/P3 non-slip approved
- Suitable for application to Solvent, UV & Latex prints
- Good UV protection

Applications

- Retail activations
- POS promotions
- Social distancing
- Directional messaging
- Exhibitions

Technical Information

Roll Width: 1.37m
Roll Length: 50m
Material: Monomeric PVC
Thickness: 80 micron
Adhesive: Clear permanent adhesive
Liner: 100gsm PEK paper with single side PE/silicon

Warranty

Pform products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Pform materials found to not meet our product specifications. In no case shall Pform or Visionary Digital be liable for any direct, indirect, or consequential damages, including labor or non Pform materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy of suitability for specific applications.

Lamination

Suitable for application to UV, solvent and Latex printed self adhesive films

Lamination Method

Cold lamination only

Durability

Durability depends on many factors including the surface it is applied to and the frequency of abrasive forces. Please see guide below;

- > Moderate Traffic - 12 months
- > High Traffic - 3 months

Slip Resistance

R9 / P3 non-slip certification
Australian / New Zealand standards AS 4586:2013

PROMO NON-SLIP FLOOR LAMINATE - R9

NON-SLIP CERTIFICATION REPORT - PAGE 1/2

www.FloorSlipTest.com.au

Unit 4/40 Bessemer St
Blacktown NSW 2148
Phone 02 9621 3706
info@SafeEnvironments.com.au



7 September 2023

Test Report No. M1675

Slip Resistance Classification of New Pedestrian Surface Materials

AS 4586-2013 Appendix A (Wet Pendulum Test)

The slip resistance classification has been determined for unused surfaces under specific conditions. Factors such as usage, cleaning systems, applied coatings and patterns of wear may affect the characteristics of the surface after classification. Standards Australia Handbook 198:2014 *Guide to the specification and testing of slip resistance of pedestrian surfaces* provides guidance for the selection of slip resistant pedestrian surfaces classified in accordance with AS 4586-2013. It is recommended that this test report be read in conjunction with AS 4586, HB 197 & HB 198.

Requested by: Visionary Digital
Client Address: 2/27 William Street
Balaclava VIC 3183
Product Manufacturer: Pform Self Adhesive Medias + Laminates Pform
Product Description: Pform Promo Non-Slip Floor Laminate

Test conducted according to: AS 4586:2013 Appendix A
Sampling Procedures: Performed by client and tested as received. 25/1
Location: Millers Road, Brooklyn VIC 3012 Nasser Cura
Conducted by:

Date: 05 September 2023 Temperature: 16°C
Sample: Unfixed Cleaning: None
Rubber slider used: Slider 96 Conditioned: Grade P 400 paper dry followed by wet lapping film
Slope of specimen: Tested on a flat level surface
Direction of Test: N/A

	Specimen 1	Specimen 2	Specimen 3	Specimen 4	Specimen 5
Mean BPN of last 3 swings:	34	38	37	41	37

Reported SRV of Sample:	37
Class:	P3

The expanded uncertainty (U_{95}) at the 95% level of confidence with a coverage factor (k) of 2 has been estimated to be 3 BPN or 8 %, whichever is the greater; sampling uncertainty has not been included. The expanded uncertainty should be considered when interpreting results or assessing conformity. Results relate only to items tested.



self adhesive vinyls + laminates

PROMO NON-SLIP FLOOR LAMINATE - R9

NON-SLIP CERTIFICATION REPORT - PAGE 2/2



www.FloorSlipTest.com.au

Unit 4/40 Bessemer St
Blacktown NSW 2148
Phone 02 9621 3706

info@SafeEnvironments.com.au



7 September 2023

Test Report No. M1675

Slip Resistance Classification of New Pedestrian Surface Materials

AS 4586-2013 Appendix D (Oil-Wet Inclining Platform Test)

The slip resistance classification has been determined for unused surfaces under specific conditions. Factors such as usage, cleaning systems, applied coatings and patterns of wear may affect the characteristics of the surface after classification. Standards Australia Handbook 198:2014 *Guide to the specification and testing of slip resistance of pedestrian surfaces* provides guidance for the selection of slip resistant pedestrian surfaces classified in accordance with AS 4586-2013. It is recommended that this test report be read in conjunction with AS 4586 and HB 198.

Requested by: Visionary Digital
Client Address: 2/27 William Street
Balaclava VIC 3183
Product Manufacturer: Pform Self Adhesive Medias + Laminates
Product Description: Pform Promo Non-Slip Floor Laminate
Surface Structure: Smooth
Fixed/Unfixed: Fixed
Joint Width: N/A

Test conducted according to: AS 4586-2013 Appendix D (Incorporating Amendment No.
Sampling Procedures: 1) Performed by client and tested as received.
Location: 4/40 Bessemer Street, Blacktown NSW 2148
Conducted by: Connor Murphy & Ratan Venkatesan
Test Shoe Type: Bergmann with LeipzigV73-SP sole form

Date: 06 September 2023
Cleaning: As Received
Air Temperature: 20°C

Displacement Space: Not Measured
Displacement Space Assessment Group: N/A

Corrected Mean Overall Acceptance Angle:	8°
Slip Resistance Assessment Group:	R9

The expanded uncertainty (U_{95}) at the 95% level of confidence with a coverage factor (k) of 2 has been estimated to be 3 degrees; sampling uncertainty has not been included. The expanded uncertainty should be considered when interpreting results or assessing conformity. Results relate only to items tested.